

HF2 Pet with Hard Floor Nozzle

PRODUCT INFO:

- HF2 Pet Hard Floor
- HF201P 011
- 39401036
- EAN 8059019084152

WEIGHT AND DIMENSIONS:

- NET WEIGHT [KG]: 2,07
- PACKED WEIGHT [KG]: 4
- PRODUCT DIMENSIONS (WxDxH) [mm]: 259*204*1103
- PACK DIMENSIONS (WxDxH) [mm]: 617*276*156

COLOR SCHEME:

- Urban Black
- Uranus Green

ACCESSORIES:

- Crevice tool
- Wall mount with cable winder and 2 screws
- Mini Power Nozzle



NEW HOOVER CORDLESS STICK HF2 with ULTRA COMPACT X3™

ULTRALIGHT CLEANING WITH SURPRISING PERFORMANCE



OUR LIGHTEST STICK



EXTENDING SUCTION POWER



BIN CAPACITY TRIPLED (1L)



MAIN FEATURES

- **Brushless motor:** 165W to generate up to **25AW¹** (standard mode)
- Runtime² Standard Mode: up to 20 min
- Runtime² Turbo Mode: up to 10 min
- **NEW ECO Mode Runtime:** up to 40 min (in Handheld configuration using the crevice tool)
- **14.4V/ 2500mAh** Lithium-Ion Battery pack supplied for 36Wh consumption
- Up to **500 LAW³** (Lasting AirWatt)
- Capable of **picking up 99%** of dust on hard floors⁴
- **ULTRA COMPACT X3™** compacting the dust to extend suction power and maximize bin capacity
- **ULTRALIGHT:** less than 1.3 kg in Handheld
- Separation System: Single Cyclone
- Bin Capacity: 0.33L tripled to **1L⁵** thanks to **ULTRA COMPACT X3™**
- **Intuitive UI** showing battery status, alerts and power mode
- **Turbo/ECO Button**
- **Integrated soft crevice** in the Handheld
- Removable and washable EPA filter
- Removable battery pack, easy to charge everywhere
- Charging time: 3.5 - 4 hours
- **hOn app** for extra contents

HARD FLOOR NOZZLE

- Main motorized nozzle with frontal LED lights ideal for Hard Floors
- Brushbar status indicator (through flashing frontal LED lights)
- **ANTI-TWIST™** to prevent hair wrapping around the brushbar
- Convenient nozzle window release and access of the brushbar from the side

¹AW measured according to IEC62885-4:2020 at tube end, with powered nozzle; based on internal tests.

²Run time measured with main motorized nozzle.

³Up to 25 AirWatt Power X 20 minutes or more Runtime. Suction power AW measured according to IEC62885-4:2020 at tube end, with powered nozzle; runtime measured with nozzle attached according to IEC62885-4:2020; based on internal tests.

⁴On flat hard floors. Tested internally according to IEC 62885-2 Clause 5.3 in turbo mode.

⁵Gross volume. Equivalent net volume 0.75L.